



PRODUCT FEATURES

NPT THREADED CONNECTION

FULL BORE

3 PIECE



PARTS / MATERIALS

NO	PART NAME	MATERIAL
1	BODY	GS-C25
2	COVER	GS-C25
3	BALL	AISI 420
4	STEM	CK 45 + GAL.
5	BALL SEAL	PTFE-Teflon
6	NECK SEAL	PTFE-Teflon
7	THROAT PRESSURE	PTFE-Teflon
8	BOWL WASHER	Ck 70
9	COUNTER NUT	5.6.
10	STUD BOLT	8.8
11	NUT	8.8
12	STOPPING PIM	St 42
13	HANDLE	St 37
14	SPINDL O-RING	VITON
15	BODY O-RING	VITON

PRODUCT



DIMENSIONS

DN	INCH	L mm	KB mm	h mm	R inch	d mm	Db mm	WEIGHT kg
DN 15	1/2"	75	125	55	1/2"	15	16	0,85
DN 20	3/4"	80	125	60	3/4"	20	16	1,4
DN 25	1"	90	135	80	1"	25	20	1,55

DESIGN

API 6D

FACE TO FACE

ASME B16.10

DIŞLI BAĞLANTISI

EN 10226-1

TEST

EN 12266-1

WORKING TEMPERATURE

-20 °C / +180 °C

APPLICATIONS



NATURAL GAS



OIL



LPG



FUEL-OIL



COMPRESSED AIR

CERTIFICATES



Dimensions are in mm. Within the relevant standards; we reserve the right to change the design and construction.